

## Guarnizioni piane METALJACK<sup>®</sup> per flange tipo RF

Diametro nominale	Diametro interno	RF					
		Flange ANSI B16.5					
DN	d	150lb	300lb	400lb	600lb	900lb	1500lb
inches		D					
1/2	21.4	47.6	54.0	54.0	54.0	63.5	63.5
3/4	27.0	57.2	66.7	66.7	66.7	69.8	69.8
1	33.3	66.7	73.0	73.0	73.0	79.4	79.4
1 1/4	42.0	76.2	82.5	82.5	82.5	88.9	88.9
1 1/2	48.4	85.7	95.2	95.2	95.2	98.4	98.4
2	60.3	104.8	111.1	111.1	111.1	142.9	142.9
2 1/2	73.0	123.8	130.2	130.2	130.2	165.1	165.1
3	88.9	136.5	149.2	149.2	149.2	168.3	174.6
3 1/2	101.6	161.9	165.1	161.0			
4	114.3	174.6	181.0	177.8	193.7	206.4	209.5
5	141.3	196.8	215.9	212.7	241.3	247.6	254.0
6	168.3	222.2	250.8	247.6	266.7	288.9	282.6
8	219.1	279.4	308.0	304.8	320.7	358.8	352.4
10	273.0	339.7	362.0	358.8	400.0	435.0	435.0
12	323.8	409.6	422.3	419.1	457.2	498.2	520.7
14	355.6	450.9	482.8	492.6	492.1	520.7	577.8
16	406.4	514.4	539.7	536.6	565.1	574.7	641.3
18	457.2	549.3	596.9	593.7	612.8	638.2	704.8
20	508.0	606.4	654.0	647.7	682.6	698.5	755.7
22	558.8	660.4	704.9	701.7	733.4		
24	609.6	717.5	774.7	768.3	790.6	838.2	901.7
26	660.4	774.0	835.0	831.9	866.8	882.6	
28	711.2	831.9	898.5	892.2	914.4	946.1	
30	762.0	882.7	952.5	946.2	971.6	1010.0	
32	812.8	939.8	1006.0	1003.0	1022.0	1073.0	
34	863.6	990.6	1057.0	1054.0	1073.0	1137.0	
36	914.4	1047.8	1118.0	1118.0	1130.0	1200.0	
38	965.2	1111.3					
40	1016.0	1162.1					
42	1066.8	1219.2					
44	1117.5	1276.0					
46	1169.6	1327.0					
48	1220.0	1384.0					
50	1270.0	1435.0					
52	1320.0	1492.0					
54	1372.0	1549.0					
56	1422.0	1606.0					
58	1475.0	1663.0					
60	1525.0	1714.0					

Tutte le dimensioni sono in mm

Diametro nominale	Diametro interno	RF							
		Flange UNI 2229 - DIN 2690							
DN	d	PN 2.5	PN 6	PN 10	PN 16	PN 25	PN 40	PN 64	PN 100
		D							
10	18	38	38	45	45	45	45	56	56
15	22	43	43	50	50	50	50	61	61
20	28	53	53	60	60	60	60	72	72
25	35	63	63	70	70	70	70	82	82
32	43	75	75	82	82	82	82	88	88
40	49	85	85	92	92	92	92	103	103
50	61	95	95	107	107	107	107	113	120
65	77	115	115	127	127	127	127	138	145
80	90	132	132	142	142	142	142	148	155
100	115	152	152	162	162	168	168	175	180
125	141	182	182	192	192	195	195	210	217
150	169	207	207	218	218	225	225	247	257
(175)	195	237	237	248	248	255	267		
200	220	262	262	273	273	285	292	309	324
250	274	318	318	328	330	342	353	364	391
300	325	373	373	378	385	402	418	424	458
350	368	423	423	438	445	458	475	486	512
400	420	473	473	490	497	515	547	588	627
450	470	528	528	540	557	565	572	657	704
500	520	578	578	595	618	625	628	764	813
600	620	680	680	695	735	730	745	879	950
700	720	785	785	810	805	830	850	988	
800	820	890	890	915	910	940	970	1108	
900	920	990	990	1015	1010	1040	1080	1220	
1000	1020	1090	1090	1120	1125	1150	1190		
1200	1220	1290	1305	1340	1340	1360	1395		
1400	1420	1490	1520	1545	1540	1575	1615		
1600	1620	1700	1720	1770	1760	1795	1830		
1800	1820	1900	1930	1970	1960	2000			
2000	2020	2100	2135	2180	2165	2230			
2200	2220	2305	2345	2380	2375				
2400	2420	2505	2555	2590	2585				
2600	2620	2705	2760	2790	2785				
2800	2820	2920	2970	3010					
3000	3020	3120	3170	3225					
3200	3220	3320	3380						
3400	3420	3520	3590						
3600	3620	3730	3800						
3800	3820	3930							
4000	4020	4130							

TOLLERANZE	
≤ 600	> 600
d ± 0.4	+ 0 d - 3.2
D ± 0.4	+ 0 D - 3.2

